

Compiler

[[Go Back](#)]

Cooperscript Parsing

Parser uses following sets of initial chars. (in parentheses or on separate line) to help determine class of tokens encountered.

- Alpha:
 - keyword (a-z)
 - built-in function (a-z)
 - system function* (_)
- Identifiers:
 - local variable (A-Z, _)
 - field (A-Z, _)
 - method (A-Z, _)
 - class (A-Z, _)
- Numeric:
 - 0-9, -
- Punctuation:
 - (,), {, }, #, ", \$, ;
- Operators:
 - +, -, *, /, %, &, |, ^, ~, =, !, <, >, :, ?
- Invalid:
 - Literal Chars. (\, .)
 - Symbols ([,], ', ` , @, comma)

* System function names begin and end with 2 consecutive underscores. User-defined identifiers begin with optional single underscore followed by a letter, and may contain letters of both cases. The other 3 types of identifiers (keywords, built-in functions, system functions) contain lower case letters only.

Oddball characters:

- (\) backslash found only in string literals
- (.) period found only in numeric literals
- (-) hyphen found at beginning of numeric literals and 3 operators: negate, subtract, -=
- (}) close brace in string literal must be escaped

Lexical Scanner (Summary)

Each bottom-level category followed by (n), where n = count, category omitted if zero.

- ALPHA
 - KEYWORD
 - BLTINFUNC
 - SYSFUNC
 - IDENTIFIER
- NUMERIC
 - BINARY
 - OCTAL
 - HEXADECIMAL
 - DECIMAL
 - LONG
 - FLOAT
- PUNCT
 - OPENPAR
 - CLOSEPAR
 - SEMICOLON
 - CMTLINE
 - CMTBLK
 - STRLIT
 - OPERATOR
- INVALID
 - ERRSYM
 - ERRESC
 - ERRDOT
- Error messages:
 - Line no., description

Lexical Scanner (Detail)

```
LN # TYP VAL CNV
==== === === ===
      XXX xxx xxx
0001 [ line buf one ]
      KWD str op
      FUN str
      SYS str
      ID str
0002 [ line buf two ]
      BIN str dec
      OCT str dec
      HEX str dec
      DEC dec dec
      LNG dec dec
      FLT str val
0003 [ line buf three ]
      PAR (
      PAR )
      PAR ;
      CMT {
      CMT }
      CMT #
      STR str
      OP str name
      ERR str desc
      [ omit blank lines ]
```

Each 4-digit line no. followed by contents of line in square brackets, followed by tokens, one per line.
Global boolean: summary/detail

Code Execution

All Cooperscript source code is in Polish notation, in which operators precede their operands. The following algorithm is used, in which operators are stored in one stack and operands in a separate stack. Executable code consists of tree nodes.

```
rightp = root
while true do
  if rightp = 0 then
    op = pop operator
    if op = root then
      return true
    if op = while/for/loopbody then
      pop rightp from operator stack
      continue
    if op = if then
      pop rightp from operator stack
      pop (
      continue
    if op = block then
      pop (
      pop if from operator stack
      pop (
      pop rightp from operator stack
      continue
  count = 0
  while true do
    pop operand
    if open parenthesis then break
    push operand on operator stack
    increment count
  if op = call then
    rightp = handlecall(count)
    continue
  if op = constructor then
    rightp = handlecons(count)
    continue
  if op = callback then
    rightp = handlecallback(count)
    continue
  pop operand from operator stack
  push operand
  repeat count - 1 times
    pop operand from operator stack
    push operand
    rightpop = pop
    leftpop = pop
    push op(leftpop, rightpop)
    // (: obj attridx) => obj...
  if count = 1 then
    if unary op then
      push op(pop)
    else
      rightpop = pop
```

```

        leftpop = pop
        push op(leftpop, rightpop)
    pop rightp from operator stack
    continue
currnode = getnode(rightp)
if open parenthesis then
    push on operand stack
    push rightp on operator stack
    rightp = currnode.downp
else if operand then
    push on operand stack
    rightp = currnode.rightp
else if operator then
    push on operator stack
    rightp = currnode.rightp
else if funcbody then
    handlebody
    rightp = currnode.rightp
else if endfunc then
    pop downto begin from operator stack
    pop rightp from operator stack
else if while/for then
    rightp = currnode.rightp
    push rightp, while/for on operator stack
else if do then
    flag = pop
    if not flag then
        pop while, rightp from operator stack
        pop rightp from operator stack
        pop (
else if continue then
        pop downto while from operator stack
        pop rightp from operator stack
else if break then
        pop downto while from operator stack
        pop rightp, rightp from operator stack
        pop (
else if breakfor then
        pop downto for from operator stack
        pop rightp, rightp from operator stack
        pop (
        pop (
else if contfor then
        pop downto loopbody from operator stack
        pop rightp from operator stack
else if then then
    flag = pop
    if flag then
        rightp = currnode.rightp
    else
        pop if from operator stack
        pop (
        pop rightp from operator stack

```

```

else
  return false

pop downto x from operator stack: // handle pop-downto
  pop multiple from operator stack
  if: pop (
  while: pop (

do block while flag: // handle do-while loop
  while true do block if not flag then break

handlecons(count):
  pop classref from operator stack
  gen objref: root 0/1 = instance/class vars
  push objref on operator stack
  return handlecall(count)

handlecall(count):
  pop objref from operator stack
  push objref
  pop codept from operator stack
  return handlecodept(codept, count)

handlecodept(codept, count):
  repeat count - 2 times
    pop val from operator stack
    push val
  push count - 1
  return codept

handlecallback(count):
  pop callback from operator stack
  unpack objref, codept
  push objref
  return handlecodept(codept, count)

```